UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/775,486	02/10/2004	Kireeti Kompella	Juniper-22-1 (JNP-0302)	1048	
26479 STRAUB & PC	7590 04/28/200 OKOTYLO	9	EXAMINER		
788 Shrewsbury TINTON FALI	y Avenue	KRISHNAN, VIVEK V			
IINION FALI	LS, NJ 07724		ART UNIT	PAPER NUMBER	
			2445		
			MAIL DATE	DELIVERY MODE	
			04/28/2009	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

		Applicat	tion No.	Applicant(s)		
Office Action Summary		10/775,4	486	KOMPELLA, KIREETI		
		Examine	er	Art Unit		
		Vivek Kr	ishnan	2445		
Period fo	The MAILING DATE of this commun or Reply	cation appears on ti	he cover sheet witl	h the correspondence ac	ddress	
A SH WHIC - Exter after - If NC - Failu Any r	ORTENED STATUTORY PERIOD FOR CHEVER IS LONGER, FROM THE MINISTRATE IS LONGER IN THE MONTHS FROM THE MINISTRATE IS LONGER IN THE MONTH IS LONGER IN THE MONTH IN	AILING DATE OF T of 37 CFR 1.136(a). In no e unication. tutory period will apply and will, by statute, cause the ap	THIS COMMUNIC, event, however, may a rep will expire SIX (6) MONT oplication to become ABA	ATION. Oly be timely filed HS from the mailing date of this of NDONED (35 U.S.C. § 133).	•	
Status						
	Responsive to communication(s) file This action is FINAL . Since this application is in condition closed in accordance with the practic	2b)∏ This action is for allowance excep	non-final. ot for formal matte	•	e merits is	
Dispositi	on of Claims					
5)□ 6)⊠ 7)⊠ 8)□ Applicati	Claim(s) <u>1-53</u> is/are pending in the at 4a) Of the above claim(s) is/a Claim(s) is/are allowed. Claim(s) <u>1-15,18-41 and 44-53</u> is/are Claim(s) <u>16,17,42 and 43</u> is/are objection Papers The specification is objected to by the	re withdrawn from cere rejected. cted to. tion and/or election				
_	The drawing(s) filed on is/are: Applicant may not request that any object Replacement drawing sheet(s) including The oath or declaration is objected to	ction to the drawing(s) the correction is requ	be held in abeyand ired if the drawing(s	e. See 37 CFR 1.85(a). i) is objected to. See 37 C	, ,	
Priority ι	ınder 35 U.S.C. § 119					
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 						
2) Notic 3) Inform	t(s) se of References Cited (PTO-892) se of Draftsperson's Patent Drawing Review (Pmation Disclosure Statement(s) (PTO/SB/08) r No(s)/Mail Date	TO-948)	Paper No(s)	nmary (PTO-413) /Mail Date ormal Patent Application -		

Art Unit: 2445

DETAILED ACTION

This action is responsive to the Amendment/Arguments filed on January 27, 2009. Claims 1, 2, 12, 13, 16-18, and 27-44 have been amended. Claims 50-53 have been added. Claims 1-53 are pending.

Response to Arguments

1. Applicant's arguments with respect to Claim Rejections under 35 U.S.C. 103(a) have been fully considered but they are not persuasive and/or are moot in view of the new ground(s) of rejection.

As to Applicant's arguments with respect to Claims 1 and 27:

a. Applicant alleges that the list of neighbor interfaces does not indicate status of at least two different protocols.

Examiner respectfully disagrees. Comer (Figure 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message) provides a message including the status of at least two different protocols. The list of neighbor interfaces, as taught by Sandick (4.2 Parameters and B.1 FLIP Advertisement Message), serves as data indicative of a state (up or down) and is in fact the purpose of the message.

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

Art Unit: 2445

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

- 3. Claims 1-15, 19-41, 45-49, 50, and 52 are rejected under 35 U.S.C. 103(a) as being unpatentable over <u>Internetworking with TCP/IP</u> to Comer and further in view of <u>Internet-Draft</u>

 <u>Fast Liveness Protocol</u> to Sandick et al. (hereinafter "Sandick") (IDS submitted on July 12, 2004).
- 4. As to Claims 1 and 27, Comer discloses for use with a node, a method and apparatus (referenced hereinafter as the method) comprising:
- a) accepting, using the node, status information from at least two different protocols (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses determining at a first node status information for both BGP and TCP protocols);
- b) composing, using the node, an aggregated message including the status information from the at least two different protocols [...] (Comer; Figure 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses composing an aggregated keepalive message including the status information); and
- c) sending, using the node, the aggregated message towards a neighbor node (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses sending the keepalive message to neighbor second node).

Comer does not explicitly disclose, however Sandick discloses including the status information from the at least two different protocols as data within the aggregated message (Sandick; 4.2 Parameters and B.1 Flip Advertisement Message; list of neighbor interfaces as data in the message that indicates the status of the interfaces).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify status information and an aggregated message, as disclosed by Comer, to include explicitly indicating multiple statuses as data within the aggregated message, as disclosed by Sandick, in order to employ known methods of explicitly indicating status in a message.

- 5. As to Claims 2 and 28, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Sandick further discloses:
- d) maintaining, using the node, a first timer for tracking a send time interval, wherein the acts of composing the aggregated message and sending the aggregated message are performed after expiration of the first timer (Sandick; 4.2 Parameters and 5.3 Finite State Machine for Hello Message Exchange, discloses maintaining a HelloInterval timer to determine how often FLIP hello messages should be sent); and
- e) restarting, using the node, the first timer after the aggregated message is sent (Sandick; 4.2 Parameters and 5.3 Finite state machine for Hello Message Exchange, discloses restarting the timer after the message is sent).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify composing and sending an aggregated message, as disclosed by Comer, to

include a send time interval and associated first timer, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection (Sandick; Abstract and 4.2 Parameters).

6. As to Claims 3 and 29, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Sandick further discloses wherein the aggregated message further includes a dead time interval, and wherein the send time interval is less than the dead time interval (Sandick; 4.2 Parameters and 5.3 Finite State Machine for Hello Message Exchange, discloses a PeerDeadInterval, included in a FLIP Advertisement, that is larger than the HelloInterval and that indicates how long a device should wait from the last Hello before declaring a neighbor failure).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify an aggregated message, as disclosed by Comer, to include a dead time interval which is greater than the send time interval, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection (Sandick; Abstract and 4.2 Parameters).

7. As to Claims 4 and 30, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Sandick further discloses discloses wherein the aggregated message further includes a dead time interval, and wherein the send time interval is no more than one third of the dead time interval (Sandick; 4.2 Parameters and 5.3 Finite State Machine for Hello Message Exchange, discloses a PeerDeadInterval, included in the FLIP Advertisement, that is at least 3 times the value of the HelloInterval).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify an aggregated message, as disclosed by Comer, to include a dead time interval which is greater than 3 times the send time interval, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection and prevent erroneous declaration of a peer protocol failure in a situation where a message was lost in transmission (Sandick; Abstract and 4.2 Parameters).

8. As to Claims 5 and 31, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Sandick further discloses wherein the send time interval is less than one second (Sandick; 7.2 HelloInterval, discloses the HelloInterval default value is 3 ms).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify composing and sending a message, as disclosed by Comer, to include a send time interval that is less than one second, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection and expedite the detection and thereby the correction of a failure (Sandick; Abstract).

9. As to Claims 6 and 32, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Sandick further discloses wherein the send time interval is less than 100 msec (Sandick; 7.2 HelloInterval, discloses the HelloInterval default value is 3 ms).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify composing and sending a message, as disclosed by Comer, to include a send time interval that is less than 100 ms, as disclosed by Sandick, in order to facilitate neighbor or

peer protocol failure detection and expedite the detection and thereby the correction of a failure (Sandick; Abstract).

10. As to Claims 7 and 33, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Sandick further discloses wherein the aggregated message further includes a dead time interval (Sandick; 4.2 Parameters, discloses a PeerDeadInterval included in the FLIP Advertisement).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify an aggregated message, as disclosed by Comer, to include a dead time interval, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection (Sandick; Abstract and 4.2 Parameters).

11. As to Claims 8 and 34, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Sandick further discloses wherein the act of sending the aggregated message includes providing the aggregated message in an Internet protocol packet (Sandick; Abstract and Introduction, discloses sending a message using Internet protocol).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify sending an aggregated message, as disclosed by Comer, to include providing the message in an Internet protocol packet, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection in IP networks (Sandick; Abstract and Introduction).

12. As to Claims 9 and 35, Comer and Sandick disclose each and every limitation of claims 8 and 34. Sandick further discloses wherein the act of sending the aggregated message towards the neighbor node includes setting a destination address in the Internet protocol packet to a multicast address associated with routers that support aggregated protocol liveness (Sandick; 4.1 Neighbor Discovery, 4.2 Parameters, and 4.6 Finite State Machine for Neighbor Adjacency, discloses the sending the message as a multicast message to a neighbor node by setting the destination address to a multicast address).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify sending an aggregated message in an IP packet, as disclosed by Comer, as modified by Sandick, to include setting a destination address in the Internet protocol packet to a multicast address, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection on a subnet (Sandick; 4.1 Neighbor Discovery, 4.2 Parameters, and 4.6 Finite State Machine for Neighbor Adjacency).

- 13. As to Claims 10 and 36, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Comer further discloses wherein the neighbor node has at least one protocol peering with at least one of the at least two protocols (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses the neighbor node has at least one protocol peering with one of the protocols in the first node).
- 14. As to Claims 11 and 37, Comer and Sandick disclose each and every limitation of Claims 1 and 27. Comer further discloses wherein the status information includes a protocol state

Art Unit: 2445

selected from a group of protocols states consisting of (A) protocol up, (B) protocol down, (C) protocol not reporting, and (D) protocol restarting (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses that status of the protocol is indicated by the ability of the node or the protocol to send messages. A peer protocol receiving the message indicates that the protocol state is up, and failure to receive the message indicates the protocol state is down).

- 15. As to Claims 12 and 38, Comer discloses for use with a node, a method and elements (referenced hereinafter as the method) comprising:
 - a) receiving, using the node, an aggregated message including
 - i) for a first set of at least two different protocols of a neighbor node, status information for each of the protocols of the first set of the at least two different protocols [...] (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses receiving the BGP keepalive message including status information about the neighbor BGP and TCP), and

Comer does not explicitly disclose, however Sandick discloses including the status information from the at least two different protocols as data within the aggregated message (Sandick; 4.2 Parameters and B.1 Flip Advertisement Message; list of neighbor interfaces as data in the message that indicates the status of the interfaces) and ii) a time interval (Sandick; 4.2 Parameters, PeerDeadInterval included in the FLIP Advertisement); and

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify status information and an aggregated message, as disclosed by Comer, to include explicitly indicating multiple statuses as data within the aggregated message and to include a dead time interval, as disclosed by Sandick, in order to employ known methods of explicitly indicating status in a message and to facilitate neighbor or peer protocol failure detection (Sandick; Abstract and 4.2 Parameters).

Page 10

Comer further discloses b) updating neighbor node protocol status information using the message (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses updating TCP and BGP connection status information using the message).

16. As to Claims 13 and 39, Comer and Sandick disclose each and every limitation of Claims 12 and 38.

Sandick further discloses wherein the act of updating neighbor node protocol status information includes

i) setting, using the node, a first timer to the time interval and starting the first timer (Sandick; 5.3 Finite State Machine for Hello Message Exchange, discloses a setting a PeerDeadInterval timer to a PeerDeadInterval),

Comer further discloses ii) if the first timer expires, setting, using the node, the status of each of the protocols of the neighbor node to down (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses setting the status of the BGP

and TCP protocols of the neighbor node to down when the timer expires) (Sandick; 5.3 Finite State Machine for Hello Message Exchange, discloses setting the status of a peer protocol of the

neighbor node to down when the timer expires), and

Comer further discloses iii) if a further message, sourced from the neighbor node, and

including

A) for a second set of at least two protocols, status information for each of the

protocols of the second set, and

[...]

is received then, [...]restarting the first timer (Comer; 15.10 BGP Functionality and

Message Types and 15.16 BGP KEEPALIVE Message, discloses restarting the timer in response

to receiving a further keepalive).

Comer does not explicitly disclose, however Sandick discloses B) a new time interval and

resetting the first timer to the new time interval (Sandick; 4.2 Parameters and 5.3 Finite State

Machine for Hello Message Exchange, discloses including a PeerDeadInterval in the FLIP

Advertisements, and resetting the PeerDeadInterval timer to the time interval that is received in

the message).

It would have been obvious to one of ordinary skill in the art at the time the invention

was made to modify a further message, as disclosed by Comer, to include a dead time interval, as

disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection (Sandick;

Abstract and 4.2 Parameters).

Art Unit: 2445

17. As to Claims 14 and 40, Comer and Sandick disclose each and every limitation of Claims 13 and 39. Sandick further discloses wherein each of the time interval and the new time interval is less than one second (Sandick; 4.2 Parameters, 5.3 Finite State Machine for Hello Message Exchange, and 7.2 HelloInterval, discloses a PeerDeadInterval, included in the FLIP Advertisement, that is at least 3 times the value of the HelloInterval, which has a default value of 3 ms).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify a message, as disclosed by Comer, to include a time interval that is less than one second, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection and expedite the detection and thereby the correction of a failure (Sandick; Abstract and Introduction).

18. As to Claims 15 and 41, Comer and Sandick disclose each and every limitation of claims 12 and 38. Comer further discloses wherein the status information includes a protocol state selected from a group of protocols states consisting of (A) protocol up, (B) protocol down, (C) protocol not reporting, and (D) protocol restarting (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses that status of the protocol is indicated by the ability of the node or the protocol to send messages. A peer protocol receiving the message indicates that the protocol state is up, and failure to receive the message indicates the protocol state is down).

19. As to Claims 19 and 45, Comer discloses a method and a system (hereinafter referred to as the method) for monitoring liveness of multiple protocols, the method comprising:

- a) determining, at a first node, status information for at least two different protocols (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses determining at a first node status information for both BGP and TCP protocols);
- b) sending, from the first node, an aggregated message including the determined status information to a second node for the at least two different protocols [...] (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses sending a keepalive message indicating the status of the protocols to a second node);
- c) receiving, at the second node, the aggregated message (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses receiving the message at the second node); and
- d) updating, by the second node, first node protocol status information using the aggregated message (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses updating TCP and BGP connection status information using the message).

Comer does not explicitly disclose, however Sandick discloses including the status information from the at least two different protocols as data within the aggregated message (Sandick; 4.2 Parameters and B.1 Flip Advertisement Message; list of neighbor interfaces as data in the message that indicates the status of the interfaces).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify status information and an aggregated message, as disclosed by Comer, to

Application/Control Number: 10/775,486

Art Unit: 2445

include explicitly indicating multiple statuses as data within the aggregated message, as disclosed by Sandick, in order to employ known methods of explicitly indicating status in a message.

Page 14

20. As to Claims 20 and 46, Comer and Sandick disclose each and every limitation of Claims 19 and 45. Sandick further discloses wherein the aggregated message further includes a first time interval, and wherein the act of updating neighbor node protocol status information includes

i) setting a timer to the first time interval (Sandick; 5.3 Finite State Machine for Hello Message Exchange, discloses a setting a PeerDeadInterval timer to a PeerDeadInterval);

- ii) starting the timer (Sandick; 5.3 Finite State Machine for Hello Message Exchange, discloses a starting the PeerDeadInterval timer);
- iii) determining whether or not a further message including protocol status information is received from the first node by the second node before the expiration of the timer (Sandick; 5.3 Finite State Machine for Hello Message Exchange, discloses determining whether or not a further hello message including status information is received from the first node before the expiration of the timer); and

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify a message, as disclosed by Comer, to include determining whether a further message including protocol status information is received before the expiration of a timer, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection (Sandick; Abstract and Introduction).

Application/Control Number: 10/775,486

Art Unit: 2445

Comer further discloses iv) if it is determined that a further message including protocol status information is not received from the first node by the second node before the expiration of the timer, then informing peer protocols of the second node that the at least two protocols of the first node are down. (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses informing the BGP and TCP protocols of the second node that the BGP and TCP protocols of the first node are down when a timer expires) (Sandick; 5.3 Finite State Machine for Hello Message Exchange, discloses informing a peer protocol of the second node that the protocol of the first node is down when the timer expires).

Page 15

- 21. As to Claim 21, Comer and Sandick disclose each and every limitation of Claim 19. Comer further discloses wherein the status information includes a protocol state selected from a group of protocols states consisting of (A) protocol up, (B) protocol down, (C) protocol not reporting, and (D) protocol restarting (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses that status of the protocol is indicated by the ability of the node or the protocol to send messages. A peer protocol receiving the message indicates that the protocol state is up, and failure to receive the message indicates the protocol state is down).
- 22. As to Claim 22, Comer discloses a machine-readable medium having stored thereon a machine readable aggregated message comprising:

a) status information, for at least two different protocols of a node, of a state of each of the at least two protocols (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses sending a keepalive, with an indication of the state of the BGP and TCP protocols, this information is stored in the recipient node in order to determine connectivity and verify that the peer protocols still function); and

Comer does not explicitly disclose, however Sandick discloses including the status information from the at least two different protocols as data within the aggregated message (Sandick; 4.2 Parameters and B.1 Flip Advertisement Message; list of neighbor interfaces as data in the message that indicates the status of the interfaces) and b) a dead interval (Sandick; 4.2 Parameters and 5.3 Finite State Machine for Hello Message Exchange, discloses including a PeerDeadInterval in the message that is used by the recipient node to determine when to declare the peer protocol down)

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify status information and an aggregated message, as disclosed by Comer, to include explicitly indicating multiple statuses as data within the aggregated message and to include a dead time interval, as disclosed by Sandick, in order to employ known methods of explicitly indicating status in a message and to facilitate neighbor or peer protocol failure detection (Sandick; Abstract and 4.2 Parameters).

23. As to Claim 23, Comer and Sandick in combination disclose each and every limitation of Claim 22. Comer further discloses wherein the status information indicates a protocol state selected from a group of protocols states consisting of (A) protocol up, (B) protocol down, (C)

protocol not reporting, and (D) protocol restarting (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses that status of the protocol is indicated by the ability of the node or the protocol to send messages. A peer protocol receiving the message indicates that the protocol state is up, and failure to receive the message indicates the protocol state is down).

24. As to Claim 24, Comer and Sandick in combination disclose each and every limitation of Claim 22. Sandick further discloses c) an identifier of the node (Sandick; 1.0 Terminology, 5.1 Protocol Description, 5.2 Hello Message Contents, 5.3 Finite State Machine for Hello Message Exchange, discloses including the address of the node in the message that is used by the recipient node to determine the status of a particular peer).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the data structure, as disclosed by Comer, to include an identifier of the node, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection in IP networks (Sandick; Abstract and Introduction).

25. As to Claim 25, Comer and Sandick in combination disclose each and every limitation of Claim 24. Sandick further discloses wherein the node is a router and wherein the identifier is a router identifier (Sandick; 1.0 Terminology, 5.1 Protocol Description, 5.2 Hello Message Contents, 5.3 Finite State Machine for Hello Message Exchange, discloses including the address of the node, which is a router, in the message that is used by the recipient node to determine the status of a particular peer).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the data structure, as disclosed by Comer, to include an identifier of the router, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection in IP networks (Sandick; Abstract and Introduction).

26. As to Claim 26, Comer and Sandick in combination disclose each and every limitation of Claim 22. Sandick further discloses c) an interface index (Sandick; Appendix B.1, discloses including an interface index in the message that is used by the recipient node to determine the interface status of a peer).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the data structure, as disclosed by Comer, to include an interface index, as disclosed by Sandick, in order to facilitate neighbor or peer protocol failure detection in IP networks (Sandick; Abstract and Introduction).

27. As to Claim 47, Comer and Sandick disclose each and every limitation of claim 46. Comer further discloses wherein the status information includes a protocol state selected from a group of protocols states including at least (A) protocol up, (B) protocol down, (C) protocol not reporting, and (D) protocol restarting (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses that status of the protocol is indicated by the ability of the node or the protocol to send messages. A peer protocol receiving the message indicates

Art Unit: 2445

that the protocol state is up, and failure to receive the message indicates the protocol state is down).

- 28. As to Claim 48, Comer and Sandick disclose each and every limitation of Claim 1.

 Comer further discloses wherein the status information is local protocol status information

 (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses the status information is local protocol status information).
- 29. As to Claim 49, Comer and Sandick disclose each and every limitation of Claim 1. Comer further discloses wherein the status information is local status information and wherein each of the at least two different protocols is bring run locally on the node (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses the status information is local protocol status information and each of the two different protocols is being run locally on the node).
- 30. As to Claims 50 and 52, Comer and Sandick disclose the method of Claims 1 and 27. Comer further discloses wherein the status information of at least one of the at least two different protocols included in the aggregated message includes a protocol state set to protocol not reporting (Comer; 15.10 BGP Functionality and Message Types and 15.16 BGP KEEPALIVE Message, discloses that status of the protocol is indicated by the ability of the node or the protocol to send messages. A peer protocol receiving the message indicates that the protocol

Application/Control Number: 10/775,486

Art Unit: 2445

state is up, and failure to receive the message indicates the protocol state is down, a down state indicates that the protocol is not reporting).

Page 20

- 31. Claims 18 and 44 are rejected under 35 U.S.C. 103(a) as being unpatentable over Comer and Sandick as applied to claims 13 and 39 above, and further in view of US Patent No. 5,349,642 issued on September 20, 1994 to Kingdon (hereinafter "Kingdon").
- 32. As to Claims 18 and 44, Comer and Sandick in combination disclose each and every limitation of Claims 13 and 39. Comer and Sandick do not explicitly disclose, however Kingdon discloses wherein each of the aggregated message and the further message include an indication of a relative message age, and wherein the act of updating neighbor node protocol status information includes,
- iv) if the further message is received then, in addition to resetting the first timer to the new time interval and restarting the first timer, further
 - A) determining whether the further message is younger than the message, and
 - B) if it is determined that the further message is not younger than the message, then discarding the further message.

(Kingdon; Figure 5, discloses determining whether the sequence number of the further received message is less than the sequence number of the previously received message and if this is the case, discarding the further message).

Art Unit: 2445

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify updating neighbor node protocol status information, as disclosed by Comer, to include consideration of the relative message age, as disclosed by Kingdon, in order to avoid accepting older messages that may contain information that is no longer valid.

- 33. Claims 51 and 53 are rejected under 35 U.S.C. 103(a) as being unpatentable over Comer and Sandick as applied to claims 1 and 27 above, and further in view of U.S. Patent No. 7,362,700 to Frick et al. (hereinafter "Frick").
- 34. As to Claims 51 and 53, Comer and Sandick disclose the method of Claims 1 and 27. Comer and Sandick do not explicitly disclose, however Frick discloses wherein the status information of at least one of the at least two different protocols included in the aggregated message includes a protocol state set to protocol restarting (Frick; column 1 lines 60-63; LSA announces intent to perform a restart).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the status information, as disclosed by Comer, to include an indication of restarting, as disclosed by Frick. One of ordinary skill in the art at the time the invention was made would have been motivated to make this combination in order to perform a hitless restart.

Art Unit: 2445

Allowable Subject Matter

35. Claims 16, 17, 42, and 43 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Conclusion

36. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Vivek Krishnan whose telephone number is (571) 270-5009. The examiner can normally be reached on Monday through Friday from 9:00 AM to 5:30 PM EST.

Art Unit: 2445

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Glenton Burgess can be reached on (571) 276-9456. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/V. K./ Examiner, Art Unit 2445 /Patrice Winder/
Primary Examiner, Art Unit 2445